

Protect Against:



Flash Floods



Severe Storms











FLOOD BAGS & BARRIERS Patented

Everything You Need to Know

Grows to _____

Item	Flood Bags	Jumbo Flood Bags	Flood Barriers		
Activated Size	24in x 12in x 3.5in H	48 in x 12in x 3.5in H	5ft: 5ft x 6.5in x 3.5in H 10ft: 10ft x 6.5in x 3.5in H 17ft: 17ft x 6.5in x 3.5in H		
Activated Weight	32lbs	64lbs	5ft: 34lbs 10ft: 68lbs 17ft: 116lbs		
Absorbs	4gal	8gal	5ft: 4.25gal 10ft: 8.5gal 17ft: 14.5gal		

How to Use _____

- Place the Bags/Barriers in the path of oncoming flood water.
- it will absorb through material & start to swell.
- Bags & Barriers reach their full height of 3.5in in 10 mins if enough water is present.
- If a rush of water is expected or you need to stack them, pre-soaking them is recommended.
- Not for use with Salt water.



Protect Your

Property





Activates When Wet

No Sand Needed



* Place wider section of Barrier towards water, as the smaller section (wedge) prevents it from rolling. **DO NOT want water moving in this direction causing seepage in between the Barriers.

Visit us at www.quickdams.com or call 888-761-4405





How to Stack _



Stack first 2 Barriers with wedge on top of wedge & then a 3rd unit on top for stable wall.



How to Align Lengthwise_

Properly stagger with water flow direction



Squish together to minimize seepage

Brick & pyramid formation should

always be stacked higher than water*

*Jumbo Flood Bags can be stacked 4 high,

if placed against a wall

For every 1ft of height needed,

Note: For a solid base, bags should be stacked in a 1:3 ratio.

extend the base by 3ft.

Tips & Tricks

- During first activation, we recommend checking on them to make sure they are directing water as desired. Adjustments may be necessary as landscaping can alter water flow.
- Bags & Barriers should be stacked higher than water level for stability and to prevent them from floating away.
- Barriers are flexible and can be curved or wrapped.
- Barriers have a dual chamber, place wider edge towards water & smaller wedge away from water to prevent rolling out of position.
- Pre-Soaking is recommended prior to stacking or if heavy rain or water flow is expected.
- For use in the **winter/snow** months, make sure they are fully activated before freezing temperatures occur to assure maximum protection when the snow is melting. We do not recommend moving them while frozen to prevent any tearing of the outer material. Also, salt on the roads should not come in contact with Quick Dams. To help, preactivate Quick Dams with water and then wrap plastic under & over the top to prevent the salt from making contact.
- Flood Bags & Barriers will not fully activate unless enough water is present.
- Once activated by water they can be used as a barrier against other oils & chemicals.
- Leave in place for up to 6 months of ongoing protection. Shrinking will occur as they dry out, but they will swell again once re-exposed to water.
- Bags/Barriers will degrade over time and will need to be replaced.
- Direct sunlight causes the product to degrade at a rapid pace, which will result in the product feeling slimy.
- You may only drive over bags & barriers as long as they are not fully activated & the under carriage of the vehicle will not come in contact. Be sure to squish the inner contents back to normal to prevent seepage.

WARNING:

- Surfaces can be slippery when wet.
- When products are left in place too long on an unfinished porous surface, a white staining may occur called efflorescence, caused by pulling fluids & surrounding particles upwards. To avoid this, remove products from these surfaces when no longer needed.
- Porous surfaces like unfinished cement cause excessive seepage, since they are both trying to absorb water. A plastic barrier used in between, may help.
- **DO NOT CUT.** The inner contents will be exposed and will make the product unusable.
- DO NOT USE around salt water, lime, calcium or chlorine. These will cause the inner absorbent to release the water & deflate the product making it useless.

🗰 Storage & Shelf Life

- Bags & Barriers unused, have a 10+ year shelf life as long as kept dry.
- Store in sealed bag for maximum term.
- Keep on hand for immediate deployment.

🗊 How to Dispose

- Throw away in trash.
- Quick Dams are safe:
 ✓ Pet friendly
 ✓ Non-toxic
 ✓ Environmentally friendly
- Optional- great soil additive to help retain
- moisture- cut open & spread/blend contents on lawn or in garden (NOTE- area will be VERY slippery until it degrades & disappears)



LIMITED WARRANTY: SINCE THE MANUFACTURER CA	ANNOT CONTROL	THE HANDLING,	APPLICATION AND	OR USE OF THIS
PRODUCT, LIABILITY DUE TO FAILURE OF THIS PRODU	UCT IS LIMITED TO	REPLACEMENT.		





www.quickdams.com | 888-761-4405