

# PRODUCT SPECIFICATION

## SAFETYWARE 4-Ply Activated Carbon Face Mask (Earloop)

- This face mask provide nose and mouth protection against dust, pollen, bacteria and more.
- Made with premium quality Meltblown filter which offers high BFE & PFE of  $\geq 99\%$ .
- Outer layer is made of hydrophobic non-woven Polypropylene which provide good fluid splashes resistance while maintaining good breathability.
- The inner soft non-woven Polypropylene layer is hydrophilic which absorb droplets from the wearer effectively and makes the masks comfortable to wear.
- Build with activated carbon for filtration of organic vapours at nuisance level.
- Adjustable nose strip and flat elastic earloop to give basic protection to the user.
- Made by ultrasonic welding technology which provides strong bonding of mask & earloop.
- Comes with a smart pulls dispenser box which makes it convenient to pull up a mask.
- Features:
  - Soft & comfortable
  - Hypoallergenic
  - Low breathing resistance
  - Adaptable nose bar
  - Perfect fitting
  - UV sanitized
  - Disposable
- Made in Malaysia.

## APPLICATION

- Suitable for general industrial and daily personal protection.

## STORAGE

- The face mask shall maintain its properties in a closed pack and stored in a cool dry condition.

Item Code: 1412ELBLK



**SAFETYWARE SDN. BHD.** (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,  
Bukit Minyak Industrial Estate,  
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882  
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 11/09/2020

Revision: 04

Date revised: 03/09/2021

# PRODUCT SPECIFICATION

## TECHNICAL DATA

COLOR	Black
STYLE	4-Ply with earloop
SIZE	17.5 cm x 9.5 cm
FILTRATION EFFICIENCY	BFE: $\geq 99\%$ PFE: $\geq 99\%$
TESTING METHOD	ASTM F2101: Bacterial Filtration Efficiency (BFE) ASTM F2299: Particle Filtration Efficiency (PFE)
SHELF LIFE	2 years from manufacture date
PACKAGING	50 pcs/ box, 30 boxes/ carton
CARTON DIMENSION	565 mm (L) x 415 mm (W) x 348 mm (H)

**SAFETYWARE SDN. BHD.** (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,  
Bukit Minyak Industrial Estate,  
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882  
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 11/09/2020

Revision: 04

Date revised: 03/09/2021