

# ASTM DIELECTRIC FOOTWEAR

## DEEP HEEL OVERSHOES - 100% TESTED TO 20KV

ASTM Dielectric Footwear provides extra safety when climbing ladders and poles where the deep heel cavity can lock onto the rungs. These boots and overshoes are 100% waterproof and made from premium grade ozone resistant rubber. The construction is hand-layered in full-cut patterns to fit over work boots. The fabric lining makes them easy to get on and off. The sole has a durable construction with a non-skid bar tread outsole.

All of Salisbury's ASTM Dielectric Footwear conforms with ASTM F1117 and is **100% TESTED** to the electrical hazard requirements of ASTM F1116 at 20,000 volts.

ASTM Dielectric Footwear comes in four styles all with pole-climbing reinforcement patch. The **Overshoe** is available without buckles or with two buckles. The **Overboot** with adjustable side strap features a 14" height or a 17" height. The attached buckle and hardware is nonmetallic.

**NEW Improved Overshoes**-Salisbury now offers improved 51511 non-buckle overshoe and 51512 2-buckle overshoe. The improved overshoes include a bob sole with aggressive tread for better traction. The deep heel and improved arch are specially designed for climbing ladders comfortably. The wider opening allows for easier on/off.



Cat. No.	Description	Sizes in. ( mm )	Weight pr. lbs. ( kgs )
21405	17", 1 Buckle Overboot	Whole Sizes 7 - 17	5.8 ( 2.6 )
21406	14" 1 Buckle Overboot	Whole Sizes 7 - 17	5.0 ( 2.3 )
51508	Non-Buckle Overshoe	Whole Sizes 7 - 17	3.3 ( 1.5 )
51509	2 Buckle Overshoe	Whole Sizes 7 - 17	4.4 ( 2 )
51511	Bob Sole - Non-Buckle Overshoe	Whole Sizes 7 - 17	3.3 ( 1.5 )
51512	Bob Sole - 2 Buckle Overshoe	Whole Sizes 7 - 17	4.4 ( 2 )



BOB SOLE

# ASTM F2413-05 EH FOOTWEAR

## DEEP HEEL OVERSHOES, OUTSOLE TESTED TO 20KV

ASTM F2413-05 EH Deep Heel Overshoes provide extra safety when climbing ladders and poles where the deep heel cavity can lock onto the rungs. These boots and overshoes are made from an ozone resistant yellow rubber that's 100% waterproof. The construction is hand-layered in full-cut patterns to fit over work boots. The fabric lining makes them easy get on and off. The sole is an anti-skid bar tread. **The outsole of these overshoes and boots have been tested to 20,000 volts to the electrical hazard requirements of ASTM F2413-05.**

ASTM F2413-05 EH Deep Heel Overshoes come in three styles all with pole-climbing reinforcement patch. The **Storm Rubber Overshoe** is available without buckles or with two buckles. The **Full-Cut Overshoe** with adjustable side strap features a 17" height.



Anti-Skid Bar Tread



21402

Cat. No.	Sizes	Description in. ( mm )	Weight pr. lbs. ( kgs )
21402	Whole Sizes 7-17	17" ( 432 ) Overshoe	5.8 ( 2.6 )
51530	Whole Sizes 6-17	2-Buckle	4.4 ( 2 )
51581	Whole & Half Sizes 7-12, Whole Sizes 5, 6, 13-17	Storm Rubber	3.3 ( 1.5 )

## ASTM F2413-05 EH FOOTWEAR

### OVERSHOES, OUTSOLE TESTED TO 20KV

ASTM F2413-05 EH Overshoes are made from an ozone resistant yellow rubber. The construction is hand-layered in full-cut patterns to easily fit over work boots. These overshoes are 100% waterproof. The lining is fabric so they easily slip on and off. The sole is an anti-skid bar tread. **The outsole of these overshoes and boots have been tested to 20,000 volts to the electrical hazard requirements of ASTM F2413-05.**

ASTM F2413-05 EH Overshoes are available in two styles: a Storm Rubber Overshoe and an 11" 4-Buckle Arctic both with a pole-climbing reinforcement patch.



51824



Anti-Skid  
Bar Tread



31924

# SERVUS®

Cat. No.	Sizes	Description in. ( mm )	Weight pr. lbs. ( kgs )
31924	Whole Sizes 6-17	11" ( 279 ) 4-Buckle Arctic	4.6 ( 2.1 )
51824	Whole & Half Sizes 7-12 Whole Sizes 13-17	Storm Rubber	3.25 ( 1.5 )

# ASTM F2413-05 EH FOOTWEAR

## OVERSHOES, OUTSOLE TESTED TO 14KV

ASTM F2413-05 EH Overshoes are made from yellow ozone resistant rubber that's 100% waterproof. The construction is hand-layered in full-cut patterns to easily slip over work shoes. The lining is fabric so they easily slip on and off. **The outsole of these overshoes and boots have been tested to 14,000 volts to the electrical hazard requirements of ASTM F2413-05.**

ASTM F2413-05 EH Overshoes come in two styles. The **Deep Heel Lineman's Storm Rubber** has a diamond V-grip outsole and pole-climbing reinforcement patch. The **11" 4-Buckle** has an anti-skid bar tread sole and heel.



Diamond V-grip  
Outsole



51510



31910



Anti-Skid  
Bar Tread

Cat. No.	Sizes	Description in. ( mm )	Weight pr. lbs. ( kgs )
31910	Whole Sizes 7-17	11" ( 279 ) 4-Buckle	3.8 ( 1.7 )
51510	Whole & Half Sizes 6-12, Whole Sizes 13-17	Deep Heel Storm Rubber	3.1 ( 1.4 )