PRODUCT SPECIFICATION



SUPER ARMOR Flame Retardant Hood

- The two-layer construction provides enhanced protection from top to bottom, ensuring wearers are safeguarded against intense heat and flames.
- The soft and lightweight design ensures maximum comfort during use and allows for ease of movement without sacrificing protection.
- the hood is resistant to wear and tear due to its doublestitching with fire-resistant yarns.
- The high-quality elastic band fits all face sizes, providing a secure and comfortable fit, and prevents heat and flames from entering the face opening.
- Compatible with all SCBA masks to ensure additional protection and comfort while working seamlessly.

APPLICATIONS

- Firefighting
- Welding and Cutting
- Electrical Work
- Industrial Safety

TECHNICAL DATA

| MATERIAL | MAZIC FM02 (93% Para-aramid / 5% Meta-aramid / 2% Carbon) |
|---------------------------|--|
| WEIGHT | 230g/m² |
| COLOR | Grayish off-White |
| STYLE | Tube |
| HEAT RESISTANCE CHANGE | ± 3% |
| BURST STRENGTH | > 500kPa |
| STANDARD | EN13911:2017 |

LIMITATION OF USE

Before using the hood, the hazard which is happening must be subject to an incident-specific risk assessment by the user. The fire hood DOES NOT protect from the following risks:

- Fire entry or activities with the equivalent.
- fire-contact risk.
- · Chemical risks.
- · Contact with bulk flammable liquid fires.

Item Code: TK12FM01KHGW



CARE INSTRUCTION

- · Do not use chlorine bleach.
- · Do not dry clean.
- Machine wash at a temperature lower than 60°C.
- Iron at low temperature.
- · Tumble dry at low temperature.
- · Softeners suggested to be used.

STORAGE

- Whenever possible, keep it stored away form direct sunlight, which may degrade the color, and reduce the performance.
- · Keep it away from direct fume source.
- · Keep the storing places dry.

SAFETYWARE SDN. BHD. (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3, Bukit Minyak Industrial Estate,

14100 Simpang Ampat, Penang, Malaysia

Tel: +604-5023 882 | Fax: +604-5081 882 www.safetyware.com | I info@safetyware.com It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitabilit of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 26/07/2024 Revision: 00