



Michael & Associates, Inc.
246 Woodland Drive, State College, PA 16803
814-234-7042 814-235-1381 fax

Email: kevin@michaelassociates.com
URL: www.michaelassociates.com



January 29, 1999

Hearing Protective Device
Test Report Number P991A

Elvex Corporation
Attn: Roland Westerdal
7 Trowbridge Drive
P.O. Box 850
Bethel, CT 06801-0850

Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the Elvex HB-35 muff-type hearing protector (test ID P991A) worn in the over-the-head position. The specified threshold measurement data were obtained using ten normal-hearing listeners, six male and four female, with ages ranging from 19 to 45 years. These listeners were selected from a standby group of about 35 volunteers, mostly graduate students, who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.

The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given.

Michael & Associates is accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974 and ANSI S12.6-1984. These accreditation criteria encompass the requirements of international standards ISO 9002:1994 (ANSI / ASQC Q92-1987), ISO / IEC Guide 25:1990, and ISO / IEC Guide 58:1993 as suppliers of test results. This report may only be reproduced or transmitted electronically in its entirety. This report shall not be used to claim product endorsement by NVLAP or by any agency of the U.S. Government.

Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.

Kevin Michael, Ph.D.
President

1/29/99

Date

INDIVIDUAL AND SUMMARY ATTENUATION DATA FOR HEARING PROTECTIVE DEVICES

TEST METHOD: ANSI S3.19-1974
MANUFACTURER: ELVEX
MODEL: HB-35

POSITION: OH
DATE: 1/29/99
TEST ID #: P991A

FREQUENCY IN HERTZ

SUBJECT	125	250	500	1000	2000	3150	4000	6300	8000
1	15	23	32	40	39	37	40	38	40
	20	24	34	43	42	40	40	38	39
	15	24	33	43	41	36	41	40	40
2	19	24	35	40	37	38	37	45	43
	19	23	31	40	36	36	36	40	40
	19	21	31	40	36	36	39	42	43
3	18	28	36	41	37	39	34	38	41
	18	28	32	44	41	42	38	38	42
	17	24	36	41	37	38	37	40	42
4	18	25	34	35	37	37	42	41	44
	19	27	32	36	35	36	42	42	44
	17	27	31	36	37	38	40	39	44
5	16	19	32	42	39	35	36	37	37
	21	22	33	37	36	36	35	40	38
	22	25	31	43	35	35	35	39	43
6	18	26	34	37	34	35	35	41	32
	16	24	32	43	35	36	36	41	39
	15	24	34	43	35	36	41	46	38
7	16	23	33	38	36	36	39	35	38
	17	23	32	39	37	35	40	39	40
	19	26	32	40	35	36	40	41	40
8	20	26	35	40	44	41	38	42	40
	18	23	37	38	38	37	39	39	41
	16	23	33	42	42	40	38	39	37
9	15	22	27	37	35	36	32	37	39
	17	24	25	35	36	34	33	40	40
	15	24	32	35	36	37	37	40	42
10	15	24	34	46	42	37	40	39	40
	16	22	33	38	39	37	39	41	42
	22	25	34	46	40	38	37	39	41
MEANS	17.6	24.1	32.6	39.9	37.6	37.0	37.9	40.0	40.2
STD. DEV.	2.0	2.0	2.4	3.2	2.6	1.9	2.6	2.2	2.4

NRR = 28 dB

HEADBAND FORCE = 2.8 LBS

Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.


MANUFACTURER: ELVEX
MODEL: HB-35
POSITION: OH

DATE: 1/29/99
TEST ID#: P991A

Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Center Frequency in Hz	Mean Attenuation in dB	Group Attenuation in dB	Standard Deviation in dB
125	17.6	41.6	2.0
250	24.1		2.0
500	32.6	185.0	2.4
1000	39.9		3.2
2000	37.6		2.6
3150	37.0		1.9
4000	37.9		2.6
6300	40.0	80.1	2.2
8000	40.2		2.4

These data were obtained through measurements made at the laboratories of Michael & Associates, Inc., State College, PA , USA. Michael & Associates, Inc., is accredited to test to ANSI S3.19-1974 and ANSI S12.6-1984 by the National Institute of Standards and Technology (NIST) National Voluntary Laboratory Accreditation Program (NVLAP).


Kevin L. Michael, Ph.D.
President

1/29/99
Date