



HAND PROTECTION

Heat Resistant Gloves

SAFETYWARE 24 oz. Heat Resistant Hot Mill Gloves

- Protect workers in high heat applications with the Hot Mill Glove
- Features quilted palm and thumb design eliminates vulnerable seams between the palm and thumb while providing superior comfort
- Offers protection from intermittent heat of up to 100°C

| Art No. | Description | Heat Resistance | Unit |
|---------|----------------------|-----------------|-------|
| HM-88 | 24oz Hot Mill Gloves | Up to 100°C | dozen |

Safetyware



HM-88

JOMAC Flame Retardant & Heat Resistant Terry Gloves

- Featuring a heavy-duty cotton terrycloth construction that is treated with a special flame retardant
- Offers excellent protection from exposure to direct flame or heat

| Art No. | Description | Heat Resistance | Unit |
|----------|-----------------------------|-----------------|------|
| 636HRLFR | 50oz Red Lined Terry Gloves | Up to 300°C | pair |

JOMAC



636HRLFR

ANSELL Crusader Flex Gloves

- Best protection and comfort in moderate heat applications
- Features a non-woven felt insulation and a full-length heat barrier that protect the worker
- Two-piece construction provide a better finger comfort, dexterity and flexibility
- Exclusive bonded Nitrile coating which helps coating which helps to protect against abrasions, cuts, snags and punctures

| Art No. | Description | Heat Resistance | Unit |
|---------|---------------------|-----------------|------|
| 42-474 | 14", Nitrile Coated | Up to 200°C | pair |

Ansell



42-474

QRP Cleanroom (Class 100) Extreme Thermal Protection Gloves

- Exterior shell is knit from a proprietary blend of fibers, selected for excellent thermal protection, plus ultra low linting characteristics
- Free from PCB, asbestos and fiberglass hazards
- Packaged for Class 100 cleanroom applications and are anti-static, 10⁹ ohms per square surface unit
- Model 59G & 50G are designed for dry applications while model 70G is ideal for both dry & wet applications

| Art No. | Description | Heat Resistance | Unit |
|---------|----------------------|-------------------|------|
| 59G | 14", Qualatherm 1000 | - 134°C to 537°C | pair |
| 50G | 14", Qualatherm 1400 | - 134°C to 760°C | pair |
| 70G | 12", Qualatherm 450 | - 61.4°C to 232°C | pair |

QRP GLOVES
QUALITY • RELIABILITY • PERFORMANCE



59G