

PRODUCT SPECIFICATION

SAFETYWARE Full Stainless Steel Floor Mounted Emergency Shower & Eyewash Combination

- Shower head delivers 76 liters of water per minute.
- Large area covers water flow at 60", the water pattern covers 20" in diameter.
- Center of the water pattern is 16" from any obstructions.
- Eyewash delivers 12 liters of water per minute.
- Dust cover protects spray heads from airborne particulates and other contaminants.
- Ball valve is activated in one second or less.
- Hands-free stay-open valve activates in one second.
- Easily located, accessible actuator is not higher than 69" above floor.
- Comply to EN 15154-1&2 and ANSI Z358.1 Safety Standard.

TECHNICAL DATA

TYPE	With foot pedal
PIPE MATERIAL	Stainless Steel 304
SHOWER HEAD/ EYEWASH BOWL	Stainless Steel 304
SHOWER VALVE	1" Stainless Steel 304 ball valve
EYEWASH VALVE	1/2" Stainless Steel 304 ball valve
WATER SUPPLY/ OUTLET	1 - 1/4" IPS/ NPT
WATER WORKING PRESSURE	0.2 - 0.8 MPA
FLOW CONTROL	Shower head: 76 L/ min Eyewash: 12 L/ min
WATER	Clean/ leached water
ACTIVATION	Shower: Pull the rod Eyewash: Hand push the plate/ foot pedal
WEIGHT	17 kg
PACKAGING	1 each/ carton
CARTON DIMENSION	900 mm (L) x 450 mm (W) x 280 mm (H)

Item Code:
ESE1001FSS



APPLICATIONS

- Manufacturing Plants
- Laboratory
- Factories
- Work Stations
- Hospitals
- Constructions

SAFETYWARE SDN. BHD. (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,
Bukit Minyak Industrial Estate,
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 01/10/2020

Revision: 00