

Product leaflet

Product	Model designation	Ordering No.
Powered air purifying respirator	SR 500 EX	H06-2012




Product description

The SR 500 EX fan is explosion-proof and specially adapted for use in an explosive atmosphere. The SR 500 EX is included together with filters and head-tops in Sundström fan-assisted respiratory protective devices. The SR 500 EX can be used as an alternative to filter protections in all situations in which the latter are recommended. This applies particularly to situations in which the work is intensive, hot or of long-duration. The fan is equipped with filters and the filtered air is supplied through a breathing hose to the head-top. The latter is then pressurized, which prevents the surrounding pollutants from being admitted.

The SR 500 EX has the following characteristics:

- Explosion proof
- Automatic control of the air flow
- Same control button is used for starting, stopping and selection of operating conditions
- Alarm with audible/visual signals if the air flow is obstructed
- NiMH battery
- Operating time of up to six hours
- Charging time about 2 hours
- Equipped with two filters/filter combinations
- Can be used together with hoods SR 520, SR 530, SR 561, SR 562, face shield SR 540 EX, helmet with visor SR 580 or full face mask SR 200.

Technical specification

	SR 500 EX	EN 12941:1998	EN 12942:1998
Air flow rate	175/225 l/min	≥ 120 l/min	
NiMH battery	13.5 V, 2.1 Ah	-	-
Operating times at 175/225 l/min:			
With particle filter P3	6.5 h/4 h	≥ 4 h	≥ 4 h
Weight with battery and P3 filter	≈ 1840 g	≤ 3500 g	≤ 3500 g
Service temperature	-10 to +40 °C, < 90 % RH	-	-
Storage temperature	-20 to +40 °C, < 90 % RH	-	-
Low flow warning level	< 175 l/min	≤ 175 l/min	≤ 175 l/min
Assigned Protection Factor¹ w hoods, SR 540 EX, SR 580	40 (TH3)	-	-
Assigned Protection Factor¹ w SR 200	40 (TM3)	-	-
Nominal Protection Factor² w hoods, SR 540 EX, SR 580	500 (TH3)	-	-
Nominal Protection Factor² w SR 200	2000 (TM3)	-	-
Approvals	Directive	Standards	Classification/markings
	PPE 89/686/EEC ATEX 94/9/EC	EN 12941:1998, EN 12942:1998 EN 60079-0:2012, EN 60079-11:2007, EN 61241-11:2006, EN 13463-1:2009	TH3/TM3  II 2 G Ex ib IIA T3 Gb ³  II 2 G Ex ib IIB T3 Gb ⁴  II 2 D Ex ib IIIC T195°C Db ⁵ Ex ib IIA T3 Gb ³ , Ex ib IIB T3 Gb ⁴ Ex ib IIIC T195°C Db ⁵
	IECEx Scheme	IEC 60079-0:2011, IEC 60079-11:2006, IEC 61241-11:2005	
	EMC 89/336/EEC	EN 61000-6-2	

1) Specified in BS 4275 and applies generally to all approved fan-assisted respiratory protective devices, regardless of the test results.


2) According to EN 529:2005.

3) SR 500 EX together with shield SR 540 EX, helmet with visor SR 580 or full face mask SR 200 with PC visor.

4) SR 500 EX together with hoods SR 520, SR 530, SR 561, SR 562 or full face mask SR 200 with glass visor.

5) SR 500 EX together with all Sundström head tops.

Key to ATEX marking

	Explosion protection mark.
II	Equipment group (explosive atmospheres other than mines with fire damp).
2 G	Equipment category (2 = High level of protection for Zone 1, G = Gas).
2 D	Equipment category (2 = High level of protection for Zone 21, D = Dust).
Ex	Explosion protected.
ib	Type of protection (Intrinsic safety).
IIA	Gas group (Propane).
IIB	Gas group (Ethylene).
IIIC	Dust material group (zone with conductive dust).
T3	Temperature class, gas (maximum surface temperature +200°C).
T195°C	Temperature class, dust (maximum surface temperature +195°C).
Gb	Equipment Protection Level, gas (high protection).
Db	Equipment Protection Level, dust (high protection).

Key to IECEx marking

Ex	Explosion protected.
ib	Type of protection (Intrinsic safety).
IIA	Gas group (Propane).
IIB	Gas group (Ethylene).
IIIC	Dust material group (zone with conductive dust).
T3	Temperature class, gas (maximum surface temperature +200°C).
T195°C	Temperature class, dust (maximum surface temperature +195°C).
Gb	Equipment Protection Level, gas (high protection).
Db	Equipment Protection Level, dust (high protection).





Head-tops, spare parts and accessories

- | Item No. | Part |
|----------|---|
| 1. | Hood SR 561 |
| 2. | Hood SR 562 |
| 3. | Hood SR 520 M/L |
| 3. | Hood SR 520 S/M |
| 4. | Hood SR 530 |
| 5. | Face shield SR 540 EX |
| 6. | Full face mask SR 200, PC visor |
| 6. | Full face mask SR 200, glass visor |
| 7. | PU hose SR 550 for SR 200 |
| 7. | Rubber hose SR 551 for SR 200 |
| 8. | Helmet with visor SR 580 |
| 9. | Hose SR 541 for SR 540 |
| 10. | O-ring for breathing hose |
| 11. | Flat gasket for hose SR 541 |
| 12. | Flow meter SR 356 |
| 13. | Belt SR 508 EX |
| 13. | Rubber belt SR 504 EX |
| 14. | Leather belt SR 503 EX |
| 15. | Harness SR 552 EX |
| 16. | Battery SR 501 EX, 2,1 Ah |
| 17. | Battery charger SR 513 EX |
| 18. | Fan SR 500 EX, bare |
| 19. | Gasket for fan |
| 20. | Pre-filter holder SR 512 EX |
| 21. | Pre-filter SR 221 |
| 22. | Pre-filter holder SR 5153 for SR 710 |
| 23. | Particle filter P3 R, SR 510 |
| 24. | Filter adapter SR 511 |
| 25. | Particle filter P3 R, SR 710 |
| 26. | Gas filter A2, SR 518 |
| 27. | Gas filter ABE1, SR 515 |
| 28. | Gas filter A1BE2K1, SR 597 |
| 29. | Combined filter A1BE2K1-Hg-P3 R, SR 599 |
| 30. | Storage bag SR 505 |
| 31. | Steel net disc SR 336 |
| 32. | Vaseline tube |
| 33. | Plug kit |

Ordering No.

- | |
|----------|
| H06-5012 |
| H06-5112 |
| H06-0212 |
| H06-0312 |
| H06-0412 |
| H06-6012 |
| H01-1212 |
| H01-1312 |
| T01-1216 |
| T01-1218 |
| H06-8012 |
| R06-0501 |
| R06-0202 |
| R06-0506 |
| R03-0346 |
| R06-2148 |
| T06-2150 |
| T06-2149 |
| T06-2002 |
| R06-2002 |
| R06-2003 |
| R06-2001 |
| R06-0107 |
| R06-2023 |
| H02-0312 |
| R01-0604 |
| H02-1312 |
| R06-0105 |
| H02-1512 |
| H02-7012 |
| H02-7112 |
| H02-7212 |
| H02-7312 |
| T06-0102 |
| T01-2001 |
| R06-2016 |
| R06-0703 |



For more information:
 Email : info@safetyware.com
www.safetyware.com