# **PRODUCT SPECIFICATION**



## Flame Retardant Cotton Coverall

- Made from 100% cotton treated flame retardant fabric via a refine process which provide reliable flame retardant performance.
- The flame retardant properties of the fabric are tested for their wash durability after a minimum of 50 washes (tested according to EN ISO 11612:2008) and it is certified by Oeko-Tex.
- It is safe to human body, light, soft and comfortable to wear.
- - 2 front chest pockets, 2 rear hip pockets, ruler pocket and swing pocket
  - Triple stitching
  - 2 way heavy duty brass zipper
  - 6 x 1" FR reflective tapes across arms, legs and back
  - Elastic on wrists area
  - Reinforced at all points of strain

## APPLICATIONS

- Marine
- Oil and gas
- Fire fighting
- General heavy duty industry
- Welding
- Smelting
- Road rescue
- Disaster rescue

### **CARE INSTRUCTIONS**

- Turn garments inside out before wash to reduce streaking from abrasion. Fill the washer no more than 2/3 full and use high water level.
- Wash separately in a Normal or Cotton cycle with water in room temperature. Use any typical home laundry detergent. Do not use soap (tallow soap containing animal fats).
- Do not use chlorinated detergent.
- Do not use fabric softeners as they may coat fibers and mask FR performance and/or serve as fuel in the event of garment ignition.
- The use of conditioned or soft water can help improve removal of contaminants from garments. Hard water precipitates soaps can result in the build-up of calcium and magnesium salts. These can serve as fuel in the event they are exposed to a source of ignition.
- It is important that all soils and other contaminants are completely removed from garments during the wash process. This may require the use of stain removal products, such as Shout®, Spray 'n Wash®, or Zout®; or presoaking garments prior to washing. The use of hot water can often make detergents more effective in the removal of soils. If all contaminants cannot be removed in home care, garments should be dry cleaned.
- Do not over dry garments. If desired, you may press with an iron via Permanent Press/Low setting.

## TECHNICAL DATA

FABRIC MATERIAL	100% cotton treated
GRAMS	215gsm
SIZE	S - 5XL
WATER SHRINKAGE	2-3 %
STANDARDS	EN ISO 11612:2008 EN ISO 11611:2007 EN ISO 15025:2000
AVERAGE WEIGHT	700-900gsm
PACKAGING	1 each / polybag

## Item Code: FROVR600



## ITEM CODE

ITEM CODE	COLOR		
FROVR600RED	Red		
FROVR600ORG	Orange		
FROVR600NBL	Navy blue		
FROVR600DGN	Dark green		

SAFETYWARE SDN. BHD. (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3, Bukit Minyak Industrial Estate, 14100 Simpang Ampat, Penang, Malaysia

Tel: +604-5023 882 www.safetyware.com | info@safetyware.com

I Fax: +604-5081 882


Date created: 21/06/2018 Revision: 01

Date revised: 21/06/2018

# **PRODUCT SPECIFICATION**



## SIZING CHART (cm)



	SIZE									
	S	M	L	XL	2XL	3XL	4XL	5XL	DIFF (±)	
COLLAR	41	41	42	43	43	45	45	48	± 1.5	
1. SHOULDER	48	50	52	54	56	58	60	64	± 1.5	
2. CHEST	112	118	124	130	136	142	148	158	± 1.5	
3. WAIST	96	100	104	108	112	116	120	126	± 1.5	
4. BACK LENGTH	43	47	51	55	59	61	63	64	± 1.5	
5. HIP	108	114	120	126	132	138	144	150	± 1.5	
6. THIGH	58	61	63	66	68	70	73	76	± 1.5	
7. PANT LENGTH	98	100	103	106	109	111	113	117	± 1.5	
8. SLEEVE LENGTH	53	54	55.5	57	58.5	60	62	64	± 1.5	
9. CUFF	26	26	27	27	28	28	28	30	± 1.5	
10. LEG OPENING	41	43	46	49	51	53	55	56	± 1.5	

- 1. The sizing chart is for reference only.
- 2. Please note that different manufacturers size their garments based on varying measurements.
- 3. Ensure a great fit using the sizing chart as above.

Plot 237, Lengkok Perindustrian Bukit Minyak 3, Bukit Minyak Industrial Estate, 14100 Simpang Ampat, Penang, Malaysia

Tel: +604-5023 882

I Fax: +604-5081 882 www.safetyware.com | info@safetyware.com

Date created: 21/06/2018

Date revised: 21/06/2018

Revision: 01