

## EASY-GRIP BLACK

### Anti-slip overshoe



- Composition: 100% rubber.
- Professional use: For greasy, wet and slipping surfaces.
- ✓ Outstanding grip coefficient
- ✓ Stretch fit structure : 4 Sizes from 34 to 50
- ✓ Color-coded sizes : identify the size at a single glance
- ✓ Can be adapted to most kind of footwear
- ✓ Hygienic and comfortable solution
- ✓ Reusable and waterproof
- ✓ Tiger-grip® antislip sole with self cleaning studs

REF « EGN »

### Certifications

EUROPEAN DIRECTIVE :  
89/686/CE

(personal protective equipment)



EUROPEAN STANDARDS

CE certification :

0075/1344/161/07/13/0626

- NF EN ISO 20347 /2012
- NF EN 13287
- Oil resistance (FO)

**CE PPE CERTIFIED Risk II**

Certified organism:

CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

- ASTM F 2913



CANADIAN STANDARDS

- Acceptance EN ISO 13287 (SRC)

### • NF EN 13287 – Antislip properties

Certification SRC = SRA + SRB

SRB : Anti-slip coefficient on steel floors with glycerin

SRA: Anti-slip coefficient on ceramic floors with detergent

| Surface | Contact with | Standard ISO 13287 | EASY-GRIP results |
|---------|--------------|--------------------|-------------------|
| Steel   | Oil          | SRB = 0.18         | + 340% = 0.62     |
|         | Detergent    | SRA = 0.32         | +140% = 0.54      |
| Ceramic | Detergent    | -                  | 0.62              |
|         | Water        | -                  | 0.62              |

Up to

### Physico-mechanical test

| Test              | Hardness  | Abrasion resistance | Density           | Breaking traction resistance | Breaking extension | Tearing resistance |
|-------------------|-----------|---------------------|-------------------|------------------------------|--------------------|--------------------|
| Standard          |           | ISO 4649/2002       | ISO 4649/2002     | EN 12803                     | EN 12803           | ISO 34-1-Méth. A   |
| Unit              | Shore A   | Mm <sup>3</sup>     | g/cm <sup>3</sup> | daN/cm <sup>2</sup>          | %                  | daN/cm             |
| EASY-GRIP results | <b>50</b> | <b>140</b>          | <b>1,16</b>       | <b>137</b>                   | <b>603</b>         | <b>10,5</b>        |

**Antistatism:** The overshoe meets antistatic properties.

The shoe and overshoe combination must necessarily be tested by the user

### Sizes



|          | S  |    |    |    | M   |    |     |     | L   |     |    |      | XL   |      |    |   |
|----------|----|----|----|----|-----|----|-----|-----|-----|-----|----|------|------|------|----|---|
| EU Sizes | 34 | 35 | 36 | 37 | 38  | 39 | 40  | 41  | 42  | 43  | 44 | 45   | 46   | 47   | 48 | + |
| UK Sizes | 1  | 2  | 3  | 4  | 5   | 6  | 6,5 | 7   | 8   | 9   | 10 | 10,5 | 11   | 12   | 13 | + |
| US Woman | 4  | 5  | 6  | 7  | 7,5 | 8  | 8,5 | 9,5 | 10  | 11  |    |      |      |      |    |   |
| US Man   |    |    |    |    | 5,5 | 6  | 7   | 8   | 8,5 | 9,5 | 10 | 11   | 11,5 | 12,5 | 13 | + |

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

### Storage and maintenance



- Hand, machine and autoclave washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.
- Autoclave sterilization