



EC-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/2782/162/11/17/1641

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : PORTWEST CLOTHING LTD
FIELDS END BUSINESS PARK THURNSCOE SOUTH YORKSHIRE
S630JF ,ENGLAND

UK

Distributor : /

Description

PPE Type : *protective glove against mechanical risks*

Product reference : AP91

Glove description : 15 GAUGE KEVLAR LINER PVC COATING GLOVE

This product is a category II.

Available sizes : 8/M (the minimum width of the glove: 108 mm)
9/L (the minimum width of the glove: 118 mm)
10/XL (the minimum width of the glove: 126 mm)
11/2XL (the minimum width of the glove: 137 mm)

Pictures :



Reference standard :

Levels of performance / class of protection

EN 420:2003+A1:2009

-

EN 388:2016

4 4 3 1 C

The levels of performance have been measured on the palm

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from NOVEMBER 2017

NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Date of issue : November 6th, 2017

Lionel Gaudillere
PPE certification manager



www.ctcgroupe.com

cemarking@ctcgroupe.com



In application of the Directive 89/686/EEC of the 21th December 1989, concerning the alignment of member states legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France

Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 09 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Culp Chaussure Maroquinerie Ganterie
Lot 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 83775649726

PORTWEST CLOTHING LTD

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	AP91
Technical file index	:	01
Last update	:	NOVEMBER 2017

IDENTIFICATION

Reference of the product :	:	AP91
Basic model		
Technical file index :	:	01
Last update :	:	NOVEMBER 2017

Manufacturer :

PORTWEST CLOTHING LTD

FIELDS END BUSINESS PARK THURNSCOE SOUTH YORKSHIRE S630JF
,ENGLAND

UK

tel : +44 (0) 1709 894 575

fax :

Factory :

SHANGHAI RISTA LABOUR PROTECTION PRODUCTS CO.,LTD

NO.1616,LUCHEN ROAD,PUJIANG TOWN,MINHANG DISTRICT SHANGHAI
CHINA

tel: 86-21-34555871

fax: 86-21-34553354

GLOVE DESCRIPTION

Glove description :

15 GAUGE KEVLAR LINER PVC COATING GLOVE

type of coating finish : sandy

Visual description :



Field of use, Risks against which the product protects :

Protect against mechanical risks

Available sizes :

Minimum length of glove (mm)	Sizes
300	8/M (the minimum width of the glove: 108 mm)
300	9/L (the minimum width of the glove: 118 mm)
300	10/XL (the minimum width of the glove: 126 mm)
300	11/2XL (the minimum width of the glove: 137 mm)

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		BLACK	PVC	1150-1190g/m ²		1.5-1.6mm
		ORANGE	PVC	1150-1190g/m ²		1.5-1.6mm
		YELLOW	KEVLAR	150-160g/m ²	15	
Back		BLACK	PVC	1150-1190g/m ²		1.5-1.6mm
		ORANGE	PVC	1150-1190g/m ²		1.5-1.6mm
		YELLOW	KEVLAR	150-160g/m ²	15	
Cuff		ORANGE	PVC	1150-1190g/m ²		1.5-1.6mm
		YELLOW	KEVLAR	150-160g/m ²	15	
Binding		BLUE	PU			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes
Chromium VI lower than the detection limit : conform
Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	4
Tear strength resistance	3
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	C
Impact Protection	-

The levels of performance have been measured on the palm


TEST REPORTS

Laboratory	CTC	Other
EN 420	S160504841_1	
Azo	S160504841_1	
EN 388	S160403018_1 S170404610_1 S170405454_1	
OTHER	S160504841_1(PAHs TIN CAD) S170506046_1(CAD) S170100588_1(DMFu)	

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : AP91

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :



Method of marking on the glove :

PRINT ON BACK OF CUFF

Packaging :

72 PRS (12 PRS X 6 PACKAGES) per case

MEANS OF CONTROL

Raw material :the supplier must provide internal quality report for them and materials must be checked at random when they arrived at the warehouse of RISTA our factory.

Production line:QC of production line must check the raw material before using them and check the semi-products at random in every 2 hours.

The Lab:each lot of product must be tested with Satra EN388 machine and TDM100 machine

Finishing or Packaging workshop:two workers to check the appearance of every pair of glove.QC must carry out a preshipment inspection according to AQL1.5 for each lot of glove

INSTRUCTION FOR USE

PORTWEST CLOTHING LTD

FIELDS END BUSINESS PARK THURNSCOE SOUTH YORKSHIRE S630JF ,ENGLAND
UK

Glove reference : AP91

Available sizes : 8/M (the minimum width of the glove: 108 mm) 9/L (the minimum width of the glove: 118 mm) 10/XL (the minimum width of the glove: 126 mm) 11/2XL (the minimum width of the glove: 137 mm)

Glove description :

15 GAUGE KEVLAR LINER PVC COATING GLOVE

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388



4 4 3 1 C

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	4	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	C	(A to F)
Impact Protection		

Protection limit

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

For dulling during the cut resistance test, the coupe test results are only indicative while the TDM cut resistance test is the reference performance result.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.