



# PRODUCT DATA SHEET

## EX7R



# EX7R

## PRODUCT DESCRIPTION

This Ex- zone 1/21 flashlight makes work easier – not just because it weighs a mere 228 g (incl. batteries). The biggest reason is the Magnetic Switch. This on/off switch can easily be controlled with work gloves. And it's the first rechargeable flashlight for Ex- zone 1/21 with patented Advanced Focus System. The included charging cradle makes charging the lithium-ion battery easy. But with a maximum battery life of 45 hours<sup>1</sup> it will rarely need to be recharged.

- Rechargeable via charging cradle
- Magnetic Switch for easy operation with gloves and protective equipment
- Focusable
- Suitable for the highest gas and dust groups (IIC/IIIC)



### TECHNICAL DATA

Length defocused [mm]	161
Length focused [mm]	161
Head diameter [mm]	41
Tube diameter [mm]	41
Weight incl. batteries [g]	228
Weight without batteries [g]	152
Focus function	Yes
Head material	PC
Tube material	PC
Optic	Plastic lense (PMMA)
Cartridge	Yes

### POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery description	1x18650 Battery Pack 3.7V
Total battery voltage [V]	3.7
Total battery capacity [mAh]	3250
Total battery energy <sup>2</sup> [Wh]	12
Rechargeable	Yes
UN number	UN 3481
Charging time <sup>5</sup> [min]	660
Energy status indicator	Charge Indicator

### EXPLOSION PROTECTION

ATEX Certificate	Baseefa17ATEX0157
IEC Ex Certificate	IECEx BAS18.0008
Ex marking	II 2G Ex ib op is IIC T4 Gb II 2D Ex ib op is IIIC T135°C Db
Ex-Zone Gas	1
Gas Group	IIA, IIB, IIC
Temperature Class Gas	T4
Ex-Zone Dust	21
Dust Group	IIIA, IIIB, IIIC
Temperature Class Dust	135 °C

### FURTHER SPECIFICATIONS

IP class	IP66
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

### LIGHT FUNCTIONS

Low Power, Power

### LIGHT SOURCE

Amount LEDs	1
LED type	Xtreme LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

### LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]		220		50
Beam distance <sup>1</sup> [m]		140		65
Run time <sup>1</sup> [h]		10		45

### SWITCH

Rotary Switch, Magnetic Switch

### TECHNOLOGIES

Advanced Focus System<sup>3</sup>

# EX7R

## PACKAGING AND LOGISTICS



### PACKAGING INFORMATION

Type of packaging	Sleeve Box
Scope of delivery	1 set of rechargeable batteries, Belt clip, Charging base, Intelligent clip, Power supply
Item No.	500837
Customs tariff number	85131000
Color	yellow
MSRP price (€)	169.90

### SINGLE PACKAGE

Dimensions W x H x D [cm]	22 x 14.7 x 8.4
Gross weight [g]	825
GTIN-13	4058205001274

### INNER CARTON

Unit	6
Dimensions W x D x H [cm]	46 x 23.5 x 19
Gross weight [g]	5260.5
GTIN-13	4058205001281

### EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	48 x 25.5 x 45
Gross weight [kg]	11.34
GTIN-13	4058205001298

# EX7R

## ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	MSRP
Fastenings / Brackets	500957	Intelligent Clip Type G	8.90 €
Color filter / Signal caps	500958	Signal Cone 42mm	6.90 €
Charger / Cable	0412	5 Station Charging Panel	69.90 €

# EX7R

## PRODUCT SERIES

### The Ledlenser EX series

If you're working in explosive environments, safety is extremely important when it comes to electronics. Safety which is defined in the ATEX directives of the European Union. Lamps in the Ledlenser EX and iL series meet these standards in every respect. Designed specifically for contact with explosive gases, vapors and dust in the best possible groups IIC and IIIC. Featuring maximum dust and water protection, and certified to ATEX directives. Yet both lines - in accordance with the ATEX workplace directives - are designed for different types of explosion hazards. The Ex-series is suitable for areas where explosive atmospheres are regularly present (zones 0, 1, 20 or 21) and the iL- series for Zone 2/22. So you'll find the perfect lamp for any environment.

## FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If no setting is explicitly indicated, measurement is based on "energy saving mode."

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

3) EP Patent 1880139, US Patent 7,461,960

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the products of the "Solidline" series, Ledlenser K1 and Ledlenser K2. The warranty does not apply to defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: [ledlenser.com/warranty](http://ledlenser.com/warranty)

5) Charging time varies by hardware used.