

November 17, 2005      Hearing Protective Device Test Report Number Q956A Revision 0



Elvex Corp.  
Attn: Roland Westerdal  
13 Trowbridge Drive  
Bethel, CT 06801

Date of Sample Receipt: 11/4/05  
Date of Sample test: 11/14/05 – 11/17/05

Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the Elvex HB-8093 muff-type hearing protector (test ID Q956A). The specified threshold measurement data were obtained using ten normal-hearing listeners, six male and four female. These listeners were selected from a standby group of about 35 volunteers, mostly graduate students, who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.

Each of ten subjects was tested three times at each of nine test frequencies. The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given. The results presented in this report pertain to the samples tested only.

Michael & Associates is accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974 and ANSI S12.6-1997. These accreditation criteria encompass the requirements of international standards ISO 9002:1994 (ANSI / ASQC Q92-1987) and ISO / IEC Guide 17025. This report may only be reproduced or transmitted electronically in its entirety. This report shall not be used to claim product endorsement by NIST, NVLAP or by any agency of the U.S. Government. All measurement equipment are calibrated with instrumentation traceable to the NIST.

*Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

A handwritten signature in blue ink, appearing to read "Kevin Michael".

Kevin Michael, Ph.D.  
President

A handwritten date in blue ink, "11/17/05".

Date

Individual and Summary Attenuation Data for  
Hearing Protective Devices

Test Method: ANSI S3.19-1974  
 Manufacturer: Elvex  
 Model: HB-8093

Position: Cap-mount  
 Date: 11/17/05  
 Test ID # Q956A

SUBJECT	FREQUENCY IN HERTZ								
	125	250	500	1000	2000	3150	4000	6300	8000
1	20	27	35	37	34	38	43	35	38
	19	26	35	37	36	37	42	36	39
	21	27	36	38	36	36	44	36	38
2	21	26	36	41	37	38	48	37	31
	20	26	38	39	37	38	41	40	32
	18	24	33	38	35	35	42	38	37
3	15	24	32	41	32	37	36	37	34
	21	23	31	40	33	39	43	34	37
	13	23	30	41	34	42	39	37	34
4	22	25	32	38	38	42	45	39	41
	22	24	34	39	38	37	44	38	40
	22	27	32	35	38	36	42	40	43
5	17	22	35	35	32	37	43	38	38
	23	24	32	37	32	40	43	38	37
	20	25	29	36	32	38	40	39	38
6	25	25	34	37	36	38	43	33	41
	20	25	31	33	38	36	39	34	37
	20	22	33	34	32	32	42	34	37
7	19	24	28	30	36	34	36	43	41
	18	24	35	35	36	38	37	39	39
	21	24	32	33	38	35	37	36	39
8	20	26	31	35	37	41	41	34	38
	25	25	32	36	36	38	40	36	38
	22	26	33	32	36	40	46	36	39
9	24	27	35	32	32	47	42	38	36
	23	26	32	38	35	39	43	36	38
	20	21	33	34	33	41	44	37	40
10	22	27	35	35	38	36	38	33	38
	22	25	33	36	37	35	41	35	33
	21	24	31	35	37	36	36	34	32
MEANS	20.5	24.8	32.8	36.2	35.4	37.9	41.3	36.6	37.5
STD. DEV.	2.6	1.6	2.2	2.9	2.2	2.9	3.0	2.4	2.8

H,M,L = 35,32,25

NRR = 28 dB

HEADBAND FORCE = 2.8 lbs

*Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

Manufacturer: Elvex  
Model: HB-8093  
Position: Cap-mount

Date: 11/17/05  
Test ID: Q956A


Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Center Frequency in Hz	Mean Attenuation in dB	Group Attenuation in dB	Standard Deviation in dB
125	20.5	45.4	2.6
250	24.8		1.6
500	32.8		2.2
1000	36.2		2.9
2000	35.4	183.6	2.2
3150	37.9		2.9
4000	41.3		3.0
6300	36.6	74.1	2.4
8000	37.5		2.8

Test Item: Q956A



These data were obtained through measurements made at the laboratories of Michael & Associates, Inc., State College, PA, USA. Michael & Associates, Inc., is accredited to test to ANSI S3.19-1974 and ANSI S12.6-1997 by the National Institute of Standards and Technology (NIST) National Voluntary Laboratory Accreditation Program (NVLAP).

  
Kevin L. Michael, Ph.D.  
President

  
Date