

PRODUCT HIGHLIGHT

HANWEI GAS DETECTOR



Fixed Gas Detector

Item Code	: BS03
Sampling Method	: Natural diffusion
Working Voltage	: DC24V±25%
Power Consumption	: 2W
Working Temperature	: -20°C~50°C for toxic gas -40°C~70°C for combustible gas
Working Humidity	: <95%RH (no dews)
Accuracy	: ±5% FS
Response Time	: T90<30s
Dimension	: 210mm x 200mm x 105mm
Weight	: about 2kg

FEATURES :

- ATEX approved
- LED display
- Easy operation by infrared remote controller
- Two adjustable alarm level
- Modular sensor, easy for replacement
- Explosion proof design, applicable to hazardous area
- Two relay output for 4-20mA type



Portable Single Gas Detector

Item Code	: BX176
Sampling Method	: Natural diffusion
Working Temperature	: -20°C~50°C for toxic gas -40°C~70°C for combustible gas
Working Humidity	: <95%RH (no dews)
Accuracy	: ±5% FS
Response Time	: T90<30s
Alarm Sound	: ≥85dB @ 1m
Charging Time	: 4h ~ 6h
Dimension	: 104mm x 60.8mm x 30.5mm
Weight	: about 125g

FEATURES :

- Intrinsically safe
- 2000 detected records
- Two adjustable alarm level
- Calibration point adjustable
- STEL & TWA alarm for toxic gases
- Low battery alert
- Data uploading
- Password management