

Product leaflet

Product
Particle filter P3 R

Model No.
SR 510

Ordering No.
H02-1312

Product Description

The SR 510, P3 R* particle filter is designed for use in Sundström half masks, full face masks and the SR 500/ SR 500 EX fan. The filter provides protection against all types of particulate pollutants. The particle filter can easily be combined with gas filters from the Sundström filter range in order to provide protection also against gases and vapours, e.g. during spray painting. The particle filter should be combined with pre-filter SR 221, which will thereby extend the life of the particle filter.

The SR 500/SR 500 EX fan should always be used with two particle filters or two combined filters consisting of gas filters and particle filters.

*R (Re-useable): The filter is intended to be used for more than a single shift.

Overview of particle filter

Model	Application
SR 510	SR 90-2, SR 100, SR 200. Fan SR 500/SR 500 EX
SR 610	Masks with standard threads, e.g. SR 200
SR 710	Fan SR 500/SR 500 EX


See separate product leaflets.

Technical specification

	SR 510	EN 143:2000	EN 12941:1998	EN 12942:1998
Pressure drop at 30 l/min.	≈ 40 Pa	≤ 120 Pa	-	-
Pressure drop at 95 l/min.	≈ 120 Pa	≤ 420 Pa	-	-
Diameter/height	107/31 mm	-	-	-
Weight	≈ 44 g	≤ 300 g	-	-
Service temperature	-10 – +55 °C, < 90 % RH	-	-	-
Storage temperature	-20 – +40 °C, < 90 % RH	-	-	-
Filtration efficiency, paraffin oil	> 99.997 %	≥ 99.95 %	≥ 99.80 %	≥ 99.95 %

Approvals EN 143:2000, EN 12941/12942:1998

- A. Filter medium
- B. Hot-melt adhesive
- C. Marking label
- D. Filter case
- E. Gasket



Head Office

Tel: +46-(0)8-562 370 00
Fax: +46-(0)8-562 370 20

P.O. Box 10056
SE-181 10 Lidingö
Sweden

Visiting address:
Vasavägen 84
SE-181 10 Lidingö

Factory

Tel: +46-(0)8-562 370 00
Fax: +46-(0)8-562 370 60

P.O. Box 76
SE-340 14 Lagan
Sweden

Visiting address:
Västergatan 4
SE-340 14 Lagan

Sundström 
www.srsafety.se