

DT117



DELTA TEK® 5000 OVERALL

Ref. DT117



Product specifications

Overall with elasticated hood. Non-woven microporous laminate Deltatek® 5000. Fastening with zip under adhesive flap (top and bottom opening). Elasticated waist and ankles. Knitted wrist. Antistatic. Individual airtight pack.

Non woven Deltatek® 5000 microporous laminate 63 g/m².

COLOUR

White

SIZE

M, L, XL, XXL

Product Use - Risks



Antistatic



BIOLOGICAL



CHEMICAL



PARTICULES



Heavy industry



Light industry



Hygiene environment

Product's highlights & user's benefits



DELTATEK® 5000

Polyethylene film ensures better a resistance to chemical attack and better mechanical resistance (abrasion - tearing)



3-part hood

Supports head movement for increased comfort



Closure with self-adhesive flap

Very good seal



Ribbed cuffs

Good hold of the glove on the hand



Elasticated ankles



Microporous laminate

No risk of lint
Very soft



DELTATEK 5000

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 13688:2013 General requirements for protective clothing.



EN13034:2005+A1:2009 Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 equipment)
TYPE 6-B: Limited protection against liquid chemicals + biological protection Type6B



EN ISO 13982-1:2004+A1:2010 Protective clothing for use against solid particulates - Type 5 clothing
TYPE 5-B: Protection against dust (asbestos) + biological protection Type 5B



EN14126:2003+AC:2004 Protective clothing - Performance requirements and tests methods for protective clothing against infective agents



EN1073-2:2002 Protective clothing against radioactive contamination. Requirements and test methods for non-ventilated protective clothing against particulate radioactive contamination.
CLASS 1: Radioactivité - Facteur de protection 5 - Classe 1



EN1149-5:2018 Electrostatic properties - Part 5: Material performance and design requirements

:: Surface resistivity inferior or equal to 2.5×10^9 Ohms on one surface at least following EN1149-1

References

References	Bar code	COLOUR	SIZE		
DT117TM	3295249054861	White	M	20	-
DT117GT	3295249054878	White	L	20	-
DT117XG	3295249054885	White	XL	20	-
DT117XX	3295249054892	White	XXL	20	-