

# SPECIFICATION SHEET

## SAFETYWARE NeoPlus™ Heavy Duty Flocklined Neoprene Gloves

- Specially designed contoured shape ensures greater comfort.
- Improve abrasion resistance and offers greater durability due to 50% increase in thickness as compared to standard flocklined gloves.
- The patterned palm and fingers give excellent grip in both wet and dry conditions.
- Cotton flocklined offers added comfort and better absorption of perspiration.
- Specially designed shape with wider cuff for industrial use.

### CARE INSTRUCTION

- Carefully inspect the gloves before you put them on. Look for cracks, tears, holes, swelling or other damage. Chemicals can pass through even the smallest pinhole. If you spot any damage, discard the gloves.
- Wash the outside of your gloves with soap and water before you remove them. Always wash them when you take a break and when you are done for the day. Then thoroughly wash your hands.
- Put your gloves in proper container when you are finished with your task for the day.

### APPLICATIONS

- General Maintenance
- Janitorial & Cleaning
- Construction Material Handling
- General Industrial Use
- Painting
- Stripping

### TECHNICAL DATA

<b>MATERIAL</b>	Neoprene	<b>COLOR</b>	Black
<b>TYPE</b>	Cotton Flocklined	<b>CUFF</b>	Straight
<b>CONSTRUCTION</b>	Unsupported Gloves		
<b>THICKNESS</b>	0.68 ± 0.03 mm	<b>LENGTH</b>	330 ± 10 mm
<b>STANDARD</b>	CE, FDA, CFIA		
<b>PACKAGING</b>	1 pair/ polybag, 12 pairs/ bag, 144 pairs/ carton		

Item Code: NEO2813



### ITEM CODE

ITEM CODE	SIZE
NEO2813-BLK-SM	S
NEO2813-BLK-MD	M
NEO2813-BLK-LG	L
NEO2813-BLK-XL	XL

### PERFORMANCE PROPERTIES

<b>EN388</b>	<b>ABRASION</b>	2
	<b>CUT</b>	1
	<b>TEAR</b>	1
	<b>PUNCTURE</b>	1
	<b>TDM CUT</b>	X

<b>EN374-1</b>	<b>B</b>	Acetone	<b>O</b>	Ammonium Hydroxide 25%
	<b>K</b>	Sodium Hydroxide 40%	<b>P</b>	Hydrogen Peroxide 30%
	<b>L</b>	Sulfuric Acid 96%	<b>T</b>	Formaldehyde 37%

Tested in accordance with  
EN ISO 374-5:2016



It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 14/02/2019

Revision: 01

Date revised: 05/04/2022

**SAFETYWARE SDN. BHD.** (432971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,  
Bukit Minyak Industrial Estate,  
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882  
www.safetyware.com | info@safetyware.com