

# PRODUCT SPECIFICATION

## SAFETYWARE Adjustable Cable Lockout

- Ideal for unusual equipment that cannot be locked with traditional equipment.
- Adjustable stainless steel cable for versatile energy isolation application.
- Outer layer of the cable is coated with transparent insulating coating with UV protection.
- The outer casing is made using impact resistant engineering plastic PC.
- Able to withstand extreme temperature of -46 °C to 149 °C.
- The 4-hole design allows multiple people to lock and manage hazards at the same time.
- Can be locked with 4 padlocks in which the diameter of lock shackle must be less than 7 mm.
- Comes with high-visibility, reusable, write-on safety labels to identify those in charge, then erase for the next job.
- Feed the cable end through the points to be locked out, then back through the lockout body. Cinch it tight to remove any slack.

## APPLICATIONS

- LOTO
- Industrial
- Maintenance

## TECHNICAL DATA

<b>MATERIAL</b>	Casing: Engineering Plastic Polycarbonate Wire: 6mm Stainless Steel Wire
<b>CABLE LENGTH</b>	1.8 meter
<b>COLOR</b>	Red

Item Code: LTC101



**SAFETYWARE SDN. BHD.** (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,  
Bukit Minyak Industrial Estate,  
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882  
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 04/01/2023

Revision: 00